



PRODUCT: GRO-LAC® ACRYLIC CONCRETE CLEAR SEAL AND FINISH

CODE: 810-0010

TYPE: ACRYLIC COPOLYMER EMULSION

PRODUCT DESCRIPTION: GRO-LAC® Acrylic Concrete Clear Seal and Finish is a low sheen acrylic product designed for use over new and old, properly prepared concrete surfaces.

USES: May be used on concrete decks, floors and walls. May also be used for sealing heavy pores in concrete blocks. GRO-LAC® Acrylic Concrete Clear Seal and Finish is more commonly used as a top coat for GRO-LAC® All-Purpose Acrylic Concrete Finishes to give gloss and to improve water resistance.

APPLICATION AND CLEAN UP: Apply with paint roller, nylon brush or airless spray equipment. All surfaces to be coated must be cleaned and free of dirt, oil, wax or loose concrete. Old concrete surfaces must be water-blasted and cleaned with a good mildewicide (TSP) before application. If more sheen is desired, apply a thin top coat until desirable results are achieved. New concrete should be cured (28 days) and etched before application. Clean tools with soapy water immediately after use. Rinse well with clean water.

PRODUCT DATA

GROCO SPECIALTY COATINGS
10818 Hawn Freeway / Dallas, Texas 75217
972-286-7890 FAX 972-286-8890

www.grocosc.com



GRO-LAC® ACRYLIC CONCRETE CLEAR SEAL AND FINISH

SPECIFICATIONS: 810-0010

Solids by Weight	29.27 +/- 2.0%	
Solids by Volume	27.03 +/- 2.0%	
Theoretical Coverage (sq. ft./gal. @ 1 mil dry film)	433	
Viscosity (Krebs units @ 77 degrees F)	59-62 K.U.	
Dry Time (@ 77 degrees F)	Touch	35-40 min.
	Re-Coat	2-4 hrs.
Gloss (@ 60 degrees F)	40-45	

AVAILABILITY:

Colors: Clear

PRECAUTIONS: Protect from freezing. Keep out of the reach of children.

FOR FURTHER INFORMATION SEE MSDS SHEET.

PRODUCT DATA

GROCO SPECIALTY COATINGS
10818 Hawn Freeway / Dallas, Texas 75217
972-286-7890 FAX 972-286-8890

www.grocosc.com