



PRODUCT: GRO-LAC® QUICK DRY TO METAL ANTI-CORROSIVE
LIGHT GRAY PRIMER

CODE: 761-4105

TYPE: ACRYLIC COPOLYMER EMULSION

PRODUCT DESCRIPTION: GRO-LAC® Quick Dry To Metal Anti-Corrosive Light Gray Primer was specially formulated to meet requirements of early air dry. It has excellent early water resistance and hardness. GRO-LAC® Quick Dry To Metal Anti-Corrosive Light Gray Primer is richly pigmented and suspended in a selected blend of acrylic copolymer emulsions. It is a water-type system; therefore, it may be easily thinned with water to a desired dip or spray application.

USES: May be used on aluminum, cold rolled steel, galvanized metal, copper and most other metal substrates.

SURFACE PREPARATION: Surface to be coated must be cleaned and free of all wax, dirt, grease and any other foreign matter.

APPLICATION AND CLEAN UP: May be sprayed with conventional or airless spray equipment. Clean all equipment with clean, warm water after each use.

DRYING: May be air cured, or warm air dried.

PRODUCT DATA

GROCO SPECIALTY COATINGS
10818 Hawn Freeway / Dallas, Texas 75217
972-286-7890 FAX 972-286-8890

www.grocosc.com



**GRO-LAC® QUICK DRY TO METAL ANTI-CORROSIVE
LIGHT GRAY PRIMER**

SPECIFICATIONS: 761-4105

Solids by Weight	53.82 +/- 2.0%	
Solids by Volume	40.89 +/- 2.0%	
Theoretical Coverage (sq. ft./gal. @ 1 mil dry film)	655	
Viscosity (Krebs units @ 77 degrees F).....	83-85 K.U.	
Dry Time (@ 77 degrees F)	Touch	20-25 min.
	Re-Coat	1 hr.
Gloss (@ 60 degrees F)	N/A	

AVAILABILITY:

Colors: Light Gray

PRECAUTIONS: PROTECT FROM FREEZING! CAUTION! Close container after each use. Do not take internally. Keep out of the reach of children.

FOR FURTHER INFORMATION SEE MSDS SHEET.

PRODUCT DATA

GROCO SPECIALTY COATINGS
10818 Hawn Freeway / Dallas, Texas 75217
972-286-7890 FAX 972-286-8890

www.grocosc.com