



PRODUCT: LOW VOC DOOR AND EDGE PRIMER

CODE: 779-1319

TYPE: VINYL ACETATE / BUTYL ACRYLATE COPOLYMER

PRODUCT DESCRIPTION: Low VOC Door and Edge Primer is a highly-pigmented flat emulsified in a complex acrylic waterborne vehicle. It dries to a hard block resistant finish. This product is excellent for painting door edges and has very little shrinkage as well as good sanding qualities.

USES: May be used on Masonite hard board panels or as a wood enamel undercoater.

SURFACE PREPARATION: Surface to be coated must be cleaned and free of wax, dirt, and moisture.

APPLICATION AND CLEAN UP: Apply by spraying or roller coating. Also can be adapted for curtain coater. Reduce viscosity with water only by using no more than a half pint per gallon. All equipment should be washed with clean, warm water after each use.

PRODUCT DATA

GROCO SPECIALTY COATINGS
10818 Hawn Freeway / Dallas, Texas 75217
972-286-7890 FAX 972-286-8890

www.grocosc.com



LOW VOC DOOR AND EDGE PRIMER

SPECIFICATIONS: 779-1319

Solids by Weight	62.27 +/- 2.0%	
Solids by Volume	46.72 +/- 2.0%	
Theoretical Coverage (sq. ft./gal. @ 1 mil dry film)	749	
Viscosity (Krebs units @ 77 degrees F).....	90-95 K.U.	
Dry Time (@ 77 degrees F)	Touch	30 min. to 1 hr.
	Re-Coat	1 hr.
Gloss (@ 60 degrees F)	Flat	

AVAILABILITY:

Colors: White
Special Tints

PRECAUTIONS: PROTECT FROM FREEZING! CAUTION! Close container after each use. Do not take internally. Keep out of the reach of children.

FOR FURTHER INFORMATION SEE MSDS SHEET.

PRODUCT DATA

GROCO SPECIALTY COATINGS
10818 Hawn Freeway / Dallas, Texas 75217
972-286-7890 FAX 972-286-8890

www.grocosc.com