



**PRODUCT:** SUPER GUARD INTERIOR LATEX WALL PAINT (FLAT)

**CODE:** 100-1005

**TYPE:** VINYL ACRYLIC EMULSION

**PRODUCT DESCRIPTION:** Super Guard Interior Latex Wall Paint is a vinyl acrylic wall paint that has been carefully formulated with the finest paint raw materials, providing a well balanced, highly versatile and durable interior wall paint. One coat of Super Guard Interior Latex Wall Paint gives exceptional hide over new and previously painted interior surfaces, drying to a beautiful, flat finish that is stain resistant and completely washable.

**USES:** Especially recommended for interior walls and ceilings, painted or unpainted plaster, brick, concrete and primed metal.

**SURFACE PREPARATION:** Surface must be clean, dry, and free of dust, grease, wax, kalsomine, soap film and gloss. If grease or wax is present, wash thoroughly with water and any good household all-purpose cleaner. Prime all bare metal with one of Groco's waterborne Red Oxide Primers before applying Super Guard Interior Latex Wall Paint. For bare sheet rock, prime with Groco's Quick Wall Primer.

**APPLICATION AND CLEAN UP:** Apply thoroughly mixed paint only at temperatures above 45 degrees F. If thinning is desired, add no more than one-half pint of clear water to one gallon of paint. Super Guard Interior Latex Wall Paint may be brushed, rolled or sprayed. For best results and one coat coverage apply generously, keeping brush or roller full; avoid excessive brushing or rolling. Clean tools with soap and water immediately after use.

PRODUCT DATA

GROCO SPECIALTY COATINGS  
10818 Hawn Freeway / Dallas, Texas 75217  
972-286-7890 FAX 972-286-8890

[www.grocosc.com](http://www.grocosc.com)



**SUPER GUARD INTERIOR LATEX WALL PAINT (FLAT)**

**SPECIFICATIONS: 100-1005**

Solids by Weight .....	47.58 +/- 2.0%	
Solids by Volume .....	28.38 +/- 2.0%	
Theoretical Coverage (sq. ft./gal. @ 1 mil dry film) .....	455	
Viscosity (Krebs units @ 77 degrees F).....	90-95 K.U.	
Dry Time (@ 77 degrees F)	Touch .....	20-25 min.
	Re-Coat .....	3-4 hrs.
Gloss (@ 60 degrees F) .....	0-5	

**AVAILABILITY:**

Colors: White  
Special Tints

**PRECAUTIONS:** PROTECT FROM FREEZING! CAUTION! Close container after each use. Do not take internally. Keep out of the reach of children.

**FOR FURTHER INFORMATION SEE MSDS SHEET.**

**PRODUCT DATA**

GROCO SPECIALTY COATINGS  
10818 Hawn Freeway / Dallas, Texas 75217  
972-286-7890 FAX 972-286-8890

[www.grocosc.com](http://www.grocosc.com)