



PRODUCT: PRO HYDE INTERIOR LATEX WALL PAINT (FLAT)

CODE: 101-1005

TYPE: VINYL ACRYLIC EMULSION

PRODUCT DESCRIPTION: Pro Hyde Interior Latex Wall Paint (Flat) is a vinyl acrylic wall paint that has been carefully formulated with the finest paint raw materials, providing a well balanced, highly versatile and durable interior wall paint. One coat of Pro Hyde Interior Latex Wall Paint (Flat) gives exceptional hide over new and previously painted interior surfaces, drying to a beautiful, flat finish that is stain resistant and completely washable.

USES: Especially recommended for interior walls and ceilings, painted or unpainted plaster, brick, concrete and primed metal.

SURFACE PREPARATION: Surface must be clean, dry, and free of dust, grease, wax, kalsomine, soap film and gloss. If grease or wax is present, wash thoroughly with water and any good household all-purpose cleaner. Prime all bare metal with one of Groco's waterborne Red Oxide Primers before applying Pro Hyde Interior Latex Wall Paint (Flat). For bare sheet rock, prime with Groco's Quick Wall Primer.

APPLICATION AND CLEAN UP: Apply thoroughly mixed paint only at temperatures above 45 degrees F. If thinning is desired, add no more than one-half pint of clear water to one gallon of paint. Pro Hyde Interior Latex Wall Paint (Flat) may be brushed, rolled or sprayed. For best results and one coat coverage apply generously, keeping brush or roller full; avoid excessive brushing or rolling. Clean tools with soap and water immediately after use.

PRODUCT DATA

GROCO SPECIALTY COATINGS
10818 Hawn Freeway / Dallas, Texas 75217
972-286-7890 FAX 972-286-8890

www.grocosc.com



PRO HYDE INTERIOR LATEX WALL PAINT (FLAT)

SPECIFICATIONS: 101-1005

Solids by Weight	54.59 +/- 2.0%	
Solids by Volume	33.24 +/- 2.0%	
Theoretical Coverage (sq. ft./gal. @ 1 mil dry film)	533	
Viscosity (Krebs units @ 77 degrees F).....	90-95 K.U.	
Dry Time (@ 77 degrees F)	Touch	25-30 min.
	Re-Coat	3-4 hrs.
Gloss (@ 60 degrees F)	0-5	

AVAILABILITY:

Colors: White
Special Tints

PRECAUTIONS: PROTECT FROM FREEZING! CAUTION! Close container after each use. Do not take internally. Keep out of the reach of children.

FOR FURTHER INFORMATION SEE MSDS SHEET.

PRODUCT DATA

GROCO SPECIALTY COATINGS
10818 Hawn Freeway / Dallas, Texas 75217
972-286-7890 FAX 972-286-8890

www.grocosc.com