



PRODUCT: QUICK WALL PRIMER

CODE: 200-1005

TYPE: VINYL ACRYLIC EMULSION

PRODUCT DESCRIPTION: Quick Wall Primer is a white-pigmented vinyl acrylic latex product for effectively priming and sealing all unpainted or previously painted interior surfaces. This efficient sealer stops suction and absorption on bare plaster drywall construction. Quick Wall Primer provides the perfect foundation coat for all flat walls, semigloss or enamel finishes. Because of its fast drying properties, a two-coat job can be done in one day.

SURFACE PREPARATION: Surface must be clean, dry, and free of dust, grease, wax, kalsomine, soap film and gloss. If grease or wax is present, wash thoroughly with water and any good household all-purpose cleaner. Prime all bare metal with one of Groco's waterborne Red Oxide Primers before applying Quick Wall Primer.

APPLICATION AND CLEAN UP: Apply thoroughly mixed paint only at temperatures above 45 degrees F. If thinning is desired, add no more than a half pint of clear water to one gallon of paint. Quick Wall Primer may be brushed, rolled or sprayed. For best results and one coat coverage apply generously, keeping brush or roller full. Avoid excessive brushing or rolling. Clean tools with soap and water immediately after use.

PRODUCT DATA

GROCO SPECIALTY COATINGS
10818 Hawn Freeway / Dallas, Texas 75217
972-286-7890 FAX 972-286-8890

www.grocosc.com



QUICK WALL PRIMER

SPECIFICATIONS: 200-1005

Solids by Weight	50.71 +/- 2.0%	
Solids by Volume	38.09 +/- 2.0%	
Theoretical Coverage (sq. ft./gal. @ 1 mil dry film)	610	
Viscosity (Krebs units @ 77 degrees F).....	85-90 K.U.	
Dry Time (@ 77 degrees F)	Touch	35-40 min.
	Re-Coat	2-4 hrs.
Gloss (@ 60 degrees F)	20/60	

AVAILABILITY:

Colors: White

PRECAUTIONS: DO NOT TAKE INTERNALLY! CONTENTS MAY BE HARMFUL OR FATAL IF SWALLOWED! Use with adequate ventilation. Avoid contact with skin and eyes and avoid breathing of vapor mist. Wash hands thoroughly after each use. Keep container closed when not in use. Keep out of the reach of children.

FOR FURTHER INFORMATION SEE MSDS SHEET.

PRODUCT DATA

GROCO SPECIALTY COATINGS
10818 Hawn Freeway / Dallas, Texas 75217
972-286-7890 FAX 972-286-8890

www.grocosc.com