



TRANSSEAL® PEELABLE PROTECTIVE COATING

Product Description:

TRANSSEAL® is a mechanically strippable coating that when applied dries to a clear tough flexible vinyl film. TRANSSEAL® is designed to provide nonporous surfaces with temporary protection against environmental hazards such as acid rain, industrial fallout and salt corrosion. TRANSSEAL® is also used as a mechanical shield for protection against minor nicks, scratches, abrasions, bug tar, bird droppings and metal shavings.

TRANSSEAL® may also be used as a masking material to protect surfaces from coating overspray as well as an excellent coating for spray booth walls. TRANSSEAL® offers protection for electronic components and removes cleanly from a surface without leaving residues or generating static electricity.

Applications would include non-porous surfaces on vehicles, aircraft, aerospace components, heavy equipment, metal frame windows, finished wood furniture, boats, cultured marble, polyester/glass shower stalls and plumbing fixtures.

Application Information:

TRANSSEAL® may be spray applied or rolled on as received with no thinning required. Roller should be a short nap type while spray equipment can be air or airless.

TRANSSEAL® should be protected from freezing with applications at temperatures no lower than 65° F or higher than 160° F.

TRANSSEAL® should be stirred with moderate agitation for several minutes before each application, if this has not been done within the past 12 hours.

TRANSSEAL® may be air or forced dried and turns from a milky white liquid to a clear film when dry. (dry film in clear, white or blue)

TRANSSEAL® film may be removed with high pressure water or simply peeled off by hand.

PRODUCT DATA

GROCO SPECIALTY COATINGS
10818 Hawn Freeway / Dallas, Texas 75217
972-286-7890 FAX 972-286-8890

www.grocosc.com



TRANSSEAL® PEELABLE PROTECTIVE COATING

Product Data:

Volume of solids at applied viscosity	51%
VOC	0.0 lbs/gal
Recommended minimum dry film thickness	2 to 3 mils
Weight per gallon	9.01
Applied viscosity	61-66 KU
pH	8.0
Coverage at 2 mils dried film	400 sq. ft./gal

PRODUCT DATA

GROCO SPECIALTY COATINGS
10818 Hawn Freeway / Dallas, Texas 75217
972-286-7890 FAX 972-286-8890

www.grocosc.com