



**PRODUCT:** TRANSSEAL® SPRAY BOOTH COATING WHITE

**CODE:** 989-1005

**TYPE:** AQUEOUS POLYMERIC COATING

**PRODUCT DESCRIPTION:** TRANSSEAL® Spray Booth Coating White is a peelable maintenance coating designed for use in spray booths. This product protects the metal walls, ceiling and floors of spray booths from paint overspray. TRANSSEAL® Spray Booth Coating White reduces maintenance man-hours because it may be reapplied over unsightly paint and overspray. The white coating creates a reflective surface, producing a clean and bright work environment. The application process may be repeated 10 to 12 times before it should be mechanically removed. TRANSSEAL® Spray Booth Coating White will never become brittle and always remains strippable. This is an environmentally safe coating that contains no VOC.

**USES:** TRANSSEAL® Spray Booth Coating White may be used as a masking material to protect surfaces from paint overspray and as a spray booth coating. May be applied over galvanized metal, aluminum, steel, and other spray booth construction material.

**APPLICATION:** TRANSSEAL® Spray Booth Coating White should be spray applied as received with no thinning required. Spray equipment may be airless or also may be applied with 1/2" nap paint roller. This product should be stirred with moderate agitation for several minutes before each application, if this has not been done within the past 12 hours. (**Note:** Before applying TRANSSEAL® Spray Booth Coating White over a previously painted substrate, concrete or any porous material, always apply a thin coat of TRANSSEAL® Pre-Wax, #989-1017. This will assure easy removal of the booth coating from the substrates. TRANSSEAL® Spray Booth Coating White may be applied immediately following the application of the TRANSSEAL® Pre-Wax.)

TRANSSEAL® Spray Booth Coating White should be protected from freezing with applications at temperatures no lower than 55 degrees F or higher than 120 degrees F.

TRANSSEAL® Spray Booth Coating White may be air or force dried and dries to a bright white film.

**REMOVAL:** TRANSSEAL® Spray Booth Coating White is easily peeled off by hand.

PRODUCT DATA

GROCO SPECIALTY COATINGS  
10818 Hawn Freeway / Dallas, Texas 75217  
972-286-7890 FAX 972-286-8890

[www.grocosc.com](http://www.grocosc.com)



**TRANSSEAL® SPRAY BOOTH COATING WHITE**

**SPECIFICATIONS: 989-1005**

|  |                                      |          |
|--|--------------------------------------|----------|
| Solids by Weight .....                                     | 52.63 +/- 2.0%                       |          |
| Solids by Volume .....                                     | 50.50 +/- 2.0%                       |          |
| Theoretical Coverage (sq. ft./gal. @ 1 mil dry film) ..... | 810                                  |          |
| <u>Recommended minimum dry film thickness:</u>             |                                      |          |
| Walls (@ 270 sq. ft./gal.) .....                           | 3 mils dry film, 6 mils wet approx.  |          |
| Floors (@ 160 sq. ft./gal.) .....                          | 5 mils dry film, 10 mils wet approx. |          |
| Viscosity (Krebs units @ 77 degrees F) .....               | 60-66 K.U.                           |          |
| Dry Time (@ 77 degrees F)                                  | Touch .....                          | 30 min.  |
|  | Re-Coat .....                        | When dry |

**AVAILABILITY:**

Colors: White

**PRECAUTIONS:** PROTECT FROM FREEZING! CAUTION! Close container after each use. Do not take internally. Keep out of the reach of children.

**FOR FURTHER INFORMATION SEE MSDS SHEET.**

**PRODUCT DATA**

GROCO SPECIALTY COATINGS  
10818 Hawn Freeway / Dallas, Texas 75217  
972-286-7890 FAX 972-286-8890

[www.grocosc.com](http://www.grocosc.com)