



**PRODUCT:** TRANSSEAL® TEMPORARY MASK

**CODE:** 989-2005

**TYPE:** AQUEOUS POLYMERIC COATING

**PRODUCT DESCRIPTION:** TRANSSEAL® Temporary Mask is designed to provide nonporous surfaces with temporary protection against environmental hazards, salt corrosion, bugs, tar, metal shavings and to provide physical protection from minor nicks, scratches and abrasions. When applied, TRANSSEAL® Temporary Mask dries to a tough, flexible vinyl film that can be easily removed by using high-pressure water or by peeling manually.

**USES:** Applications would include the protection of painted surfaces on cars, trucks, tractors, bumpers, heavy equipment, metal frame windows, finished wood furniture, boats, cultured marble, polyester/glass shower stalls and plumbing fixtures. TRANSSEAL® Temporary Mask may be used as a masking material to protect surfaces from paint over-spray and as a spray booth coating.

**APPLICATION:** Always test all surfaces to be coated with TRANSSEAL® Temporary Mask by applying a small amount to an area and allowing it to dry thoroughly. On older surfaces that show oxidation, prepare surface with liquid auto wax before application. TRANSSEAL® Temporary Mask may be applied by spray or roller application as received with no thinning required. Spray equipment may be either conventional air or airless. TRANSSEAL® Temporary Mask must be protected from freezing and must be applied at temperatures no lower than 65 degrees F and no higher than 160 degrees F. This product must be stirred with moderate agitation for several minutes before using. May be dried with forced hot air or infrared heat.

PRODUCT DATA

GROCO SPECIALTY COATINGS  
10818 Hawn Freeway / Dallas, Texas 75217  
972-286-7890 FAX 972-286-8890

[www.grocosc.com](http://www.grocosc.com)



## TRANSSEAL® TEMPORARY MASK

### SPECIFICATIONS: 989-2005

Solids by Weight .....	56.62 +/- 2.0%	
Solids by Volume .....	54.61 +/- 2.0%	
Theoretical Coverage (sq. ft./gal. @ 1 mil dry film) .....	875	
Viscosity (Krebs units @ 77 degrees F).....	63-69 K.U.	
Dry Time (@ 77 degrees F)	Touch .....	1 hr.
	Re-Coat .....	N/A
Gloss (@ 60 degrees F) .....	N/A	

### AVAILABILITY:

Colors: Clear

**PRECAUTIONS:** PROTECT FROM FREEZING! CAUTION! Close container after each use. Do not take internally. Keep out of the reach of children.

**FOR FURTHER INFORMATION SEE MSDS SHEET.**

PRODUCT DATA

GROCO SPECIALTY COATINGS  
10818 Hawn Freeway / Dallas, Texas 75217  
972-286-7890 FAX 972-286-8890

[www.grocosc.com](http://www.grocosc.com)