



PRODUCT: TRANSSEAL® PROTECTIVE FILM

CODE: 989-TPF

TYPE: AQUEOUS POLYMERIC COATING IN A DRY FILM
STATE ON A POLYPROPYLENE CARRIER SHEET

PRODUCT DESCRIPTION: TRANSSEAL® Protective Film is a non-adhesive, breathable, temporary protective film. The TRANSSEAL® liquid coating has been pre-applied to a poly carrier sheet creating a ready-to-apply peelable sheet film in a variety of width sizes and lengths.

USES: TRANSSEAL® Protective Film may be used for the protection of newly painted surfaces such as automobiles from acid rain, iron filings, bird droppings, bugs and other foreign matter that might attach itself to or deteriorate the new paint finish.

APPLICATION: TRANSSEAL® Protective Film is applied by placing the film directly to the surface while the carrier sheet is still in tact on the top. Cut the film to the desired length and remove the carrier sheet. Then smooth the TRANSSEAL® Protective Film down with a smoothing brush or soft towel. Smoothing will help eliminate excess wrinkles and air bubbles. A second choice for application is to use a semi-automatic TRANSSEAL® application dispensing machine. This machine separates the carrier sheet and the TRANSSEAL® Protective Film and then rolls the carrier sheet onto a collection spool for discarding.

PRODUCT DATA

GROCO SPECIALTY COATINGS
10818 Hawn Freeway / Dallas, Texas 75217
972-286-7890 FAX 972-286-8890

www.grocosc.com



TRANSSEAL® PROTECTIVE FILM

989-TPF

AVAILABILITY: Rolls available in width sizes: 56" (TPF56750)
48" (TPF48750)
24" (TPF24750)
12" (TPF12750)
8" (TPF8750)
6" (TPF6750)
4 1/2" (TPF4.5750)
4" (TPF4750)

Length is always 750 lineal feet, unless special ordered.

3" roll sizes are available only with a minimum order of 200 rolls and customer is required to take all. For all other roll sizes above, please check for inventory availability.

FOR FURTHER INFORMATION SEE MSDS SHEET.

PRODUCT DATA

GROCO SPECIALTY COATINGS
10818 Hawn Freeway / Dallas, Texas 75217
972-286-7890 FAX 972-286-8890

www.grocosc.com