



PRODUCT: TRANSSEAL® PRE-WAX

CODE: 989-1017

TYPE: WAX EMULSION

PRODUCT DESCRIPTION: TRANSSEAL® Pre-Wax is a paraffin wax emulsion used to create a release on bathtubs and painted surfaces where extra release is required for the application of TRANSSEAL® Protective Peelable Coatings. When dry, this emulsion is very waxy and soft to the touch and it provides an excellent barrier coat for TRANSSEAL® Protective Coatings.

APPLICATION: Apply with a roller, foam brush or conventional spray equipment. Dry to film thickness of .50 mil.

CLEAN UP: Clean all equipment after use with soap and water. Do not let dry on substrates that are to be painted. If this happens, clean before painting.

PRODUCT DATA

GROCO SPECIALTY COATINGS
10818 Hawn Freeway / Dallas, Texas 75217
972-286-7890 FAX 972-286-8890

www.grocosc.com



TRANSSEAL® PRE-WAX

SPECIFICATIONS: 989-1017

Solids by Weight	34.19 +/- 2.0%	
Solids by Volume	32.27 +/- 2.0%	
Theoretical Coverage (sq. ft./gal. @ 1 mil dry film)	517	
Viscosity (Krebs units @ 77 degrees F).....	N/A	
Dry Time (@ 77 degrees F)	Touch	15-30 min.
	Re-Coat	N/A
Gloss (@ 60 degrees F)	N/A	

AVAILABILITY:

Colors: Amber

PRECAUTIONS: PROTECT FROM FREEZING! CAUTION! Close container after each use. Do not take internally. Keep out of the reach of children.

FOR FURTHER INFORMATION SEE MSDS SHEET.

PRODUCT DATA

GROCO SPECIALTY COATINGS
10818 Hawn Freeway / Dallas, Texas 75217
972-286-7890 FAX 972-286-8890

www.grocosc.com