



**PRODUCT:** TRANSSEAL® ANTI-SLIP PEELABLE FLOOR COATING

**CODE:** 989-7010

**TYPE:** PEELABLE AQUEOUS POLYMER

**PRODUCT DESCRIPTION:** TRANSSEAL® Anti-Slip Peelable Floor Coating is a membrane of aqueous polymer and micronized homopolymer aggregate blended to form an anti-slip peelable floor coating. TRANSSEAL® Anti-Slip Peelable Floor Coating dries to a uniform textured surface. This product was formulated to protect concrete floors from spray paint fallout and forms an excellent non-slip surface to walk on.

**APPLICATION:** Apply only to non-porous concrete or properly prepared concrete. Use a 1/4 or 1/2 inch roller nap for application. For best results, apply one coat at 2 1/2 mils dry film thickness and a second coat at 2 1/2 mils dry film thickness to achieve a minimum film thickness of 5 mils. Thicker coats may be applied also. For porous concrete, precoat with TRANSSEAL® Pre-Wax and let dry before applying TRANSSEAL® Anti-Slip Peelable Floor Coating.

Do not apply when concrete temperature is lower than 50 degrees F. Allow 2 to 4 hours between coats for drying. TRANSSEAL® Anti-Slip Peelable Floor Coating may be walked on when totally dry (approximately 24 hours). Replace every 2 to 3 months or when necessary.

**CLEAN UP:** Clean all tools after use with warm water.

**REMOVAL:** Lift TRANSSEAL® Anti-Slip Peelable Floor Coating at the edge and peel off. This product may also be wetted down with water and then peeled off. Discard waste in accordance with state and local laws.

PRODUCT DATA

GROCO SPECIALTY COATINGS  
10818 Hawn Freeway / Dallas, Texas 75217  
972-286-7890 FAX 972-286-8890

[www.grocosc.com](http://www.grocosc.com)



**TRANSSEAL® ANTI-SLIP PEELABLE FLOOR COATING**

**SPECIFICATIONS: 989-7010**

Solids by Weight .....	38%+/-2
Solids by Volume .....	37%+/-2
Theoretical Coverage (sq. ft./gal. @ 5 mil dry film) .....	100
Viscosity (Krebs units @ 77 degrees F).....	95-100 K.U.

**PRECAUTIONS:** PROTECT FROM FREEZING! CAUTION! Close container after each use. Do not take internally. Keep out of the reach of children.

**FOR FURTHER INFORMATION SEE MSDS SHEET.**

**PRODUCT DATA**

GROCO SPECIALTY COATINGS  
10818 Hawn Freeway / Dallas, Texas 75217  
972-286-7890 FAX 972-286-8890

[www.grocosc.com](http://www.grocosc.com)