



PRODUCT: TRANSSEAL® TOTAL WINDOW COVERING

CODE: 989-4105 White, 989-4113 Black

TYPE: AQUEOUS POLYMERIC COATING

PRODUCT DESCRIPTION: TRANSSEAL® Total Window Covering, Black or White, was formulated with the protection of window glass in the construction industry as its goal. This product is an acrylic breathable film when dried. It protects new window glass from brick mortar, cement splashes, spray paint and other foreign matter that collects on new windows during the construction period. This product may also be used in commercial buildings and strip malls during the time of interior restoration as a black-out masking to aid as a deterrent to vandalism by keeping vandals from looking through the window glass. When construction is complete, the TRANSSEAL® Total Window Covering, Black or White, may be peeled off, leaving the window ready to be cleaned with little effort.

APPLICATION: Use 1/4 in. nap paint roller, applying TRANSSEAL® Total Window Covering, Black or White, only on the windowpane surface. Do not apply to the aluminum window area or porous substrates. Do not apply in temperatures lower than 50 degrees F. Apply product 4 to 6 mils wet to achieve minimum mil thickness of 2 to 3 mils dry.

REMOVAL: Lift TRANSSEAL® Total Window Covering, Black or White, edge with window-cleaning razor blade and peel off window. This product may also be wetted down with water and then peeled off. Discard waste in accordance with state and local laws.

PRODUCT DATA

GROCO SPECIALTY COATINGS
10818 Hawn Freeway / Dallas, Texas 75217
972-286-7890 FAX 972-286-8890

www.grocosc.com



TRANSSEAL® TOTAL WINDOW COVERING

SPECIFICATIONS: **989-4105 White, 989-4113 Black**

Solids by Weight	47.89 +/- 2.0%	
Solids by Volume	45.79 +/- 2.0%	
Theoretical Coverage (sq. ft./gal. @ 1 mil dry film)	734	
Viscosity (Krebs units @ 77 degrees F).....	65-70 K.U.	
Dry Time (@ 77 degrees F)	Touch	1 hr.
	Re-Coat	N/A
Gloss (@ 60 degrees F)	N/A	

AVAILABILITY:

Colors: Black
 White

PRECAUTIONS: PROTECT FROM FREEZING! CAUTION! Close container after each use. Do not take internally. Keep out of the reach of children.

FOR FURTHER INFORMATION SEE MSDS SHEET.

PRODUCT DATA

GROCO SPECIALTY COATINGS
10818 Hawn Freeway / Dallas, Texas 75217
972-286-7890 FAX 972-286-8890

www.grocosc.com