



PRODUCT: TRANSSEAL® WINDOW PROTECTION CLEAR
(Summer Formula)

CODE: 989-4104

TYPE: AQUEOUS POLYMERIC COATING

PRODUCT DESCRIPTION: TRANSSEAL® Window Protection Clear was formulated with the protection of windows in the home construction industry as its goal. This product is an acrylic breathable film when dried. It protects new window glass from brick mortar, cement splashes, spray paint and other foreign matter that collects on new windows during the construction period. When construction is complete, the TRANSSEAL® Window Protection Clear may be peeled off, leaving the window ready to be cleaned with little effort.

APPLICATION: Use 1/4 in. nap paint roller, applying TRANSSEAL® Window Protection Clear only on the windowpane surface. Do not apply to the aluminum window area. Do not apply in temperatures lower than 50 degrees F. Apply product 4 to 6 mils wet to achieve minimum mil thickness of 2 to 3 mils dry.

REMOVAL: Lift TRANSSEAL® Window Protection Clear edge with window-cleaning razor blade and peel off window. This product may also be wetted down with water and then peeled off. Discard waste in accordance with state and local laws.

PRODUCT DATA

GROCO SPECIALTY COATINGS
10818 Hawn Freeway / Dallas, Texas 75217
972-286-7890 FAX 972-286-8890

www.grocosc.com



TRANSSEAL® WINDOW PROTECTION CLEAR
(Summer Formula)

SPECIFICATIONS: 989-4104

Solids by Weight	47.89 +/- 2.0%	
Solids by Volume	45.79 +/- 2.0%	
Theoretical Coverage (sq. ft./gal. @ 1 mil dry film)	734	
Viscosity (Krebs units @ 77 degrees F).....	65-70 K.U.	
Dry Time (@ 77 degrees F)	Touch	1 hr.
	Re-Coat	N/A
Gloss (@ 60 degrees F)	N/A	

AVAILABILITY:

Colors: Clear

PRECAUTIONS: PROTECT FROM FREEZING! CAUTION! Close container after each use. Do not take internally. Keep out of the reach of children.

FOR FURTHER INFORMATION SEE MSDS SHEET.

PRODUCT DATA

GROCO SPECIALTY COATINGS
10818 Hawn Freeway / Dallas, Texas 75217
972-286-7890 FAX 972-286-8890

www.grocosc.com